

HAND PACKING STATIONS

ERGONOMIC SOLUTION TO HAND PACKING



ERGOPACK®
Semi-Automatic Ergonomic Hand Pack Station

ERGOPACK MODELS

SPECIFICATIONS	ERGOPACK® 10	ERGOPACK® 12	ERGOPACK® 15	ERGOPACK® 20	ERGOPACK® 25	ERGOPACK® 30	ERGOPACK® XL 10	ERGOPACK® XL 15
Max. Speed	10 CPM	12 CPM	15 CPM	20 CPM	25 CPM	30 CPM	10 CPM	15 CPM
Max. Case Range	24" x 16" x 18"	20" x 13.5" x 19"	24" x 16" x 18"	24" x 16" x 18"	24" x 16" x 18"	20" x 13.5" x 18"	24" x 20" x 18"	24" x 20" x 18"
Min. Case Range	8" x 6" x 5"	8.5" x 4.75" x 4"	8" x 6" x 5"	8" x 6" x 5"	8" x 6" x 5"	8" x 6" x 5"	8" x 6" x 5"	8" x 6" x 5"
Magazine Capacity	50" ~150 Cases	50" ~150 Cases	50" ~150 Cases	50" ~150 Cases	50" ~150 Cases	50" ~150 Cases	50" ~150 Cases	50" ~150 Cases
Case Modification Available	Y	Y	Y	Y	Y	Y	Y	Y
Glue Option	N/A	N/A	N/A	ERGOPACK® 20G	ERGOPACK® 25G	ERGOPACK® 30G	N/A	ERGOPACK® XL 15G
IP 56/NEMA 4X	Y	Y	Y	Y	Y	Y	Y	Y
Std. Voltage	240V/3PH	240V/3PH	240V/3PH	240V/3PH	240V/3PH	240V/3PH	240V/3PH	240V/3PH
SCFM- 80 PSI -3/4 Supply Line	18 SCFM	14-18 SCFM	18-20 SCFM	18-20 SCFM	14-15 SCFM	15-16 SCFM	14-16 SCFM	14-16 SCFM
Footprint (2-Person)	13'6" x 9'8" x 5'7"	12'8" x 9' x 5'7"	15'2" x 9'9" x 5'7"	15'2" x 9'9" c 5'7"	15'2" x 9'9" x 5'7"	15'2" x 9'9" x 5'7"	15'9" x 10'5" x 5'7"	15'9" x 10'5" x 5'7"
Approx. Shipping Weight	~2400 lbs.	~2400 lbs.	~2400 lbs.	~2400 lbs.	~2400 lbs.	~2400 lbs.	~2400 lbs.	~2400 lbs.
Std. Finish	Steel Plus 316 is a two component, water base epoxy filled with 316 stainless steel flake. Finish Color is a Steel-It Grey and is USDA and FDA accepted.							
Std. Electrical Components	A-B CompactLogox 5380/5069 L306ER, Studio 5000 Ver. 34, and a PanelView + 7.7" Operator Interface							
Available Options	1-2-3-4 Operator Stations, Low Case, Low Tape, Extended Magazine, Casters, Stack Lights, Elevation Kits, Spare Parts							