

WRAPPING EXCELLENCE

IN EVERY TURN





OVERVIEW

In a market full of options, the OneWrap+ stands out as the perfect blend of reliability, efficiency, and value.

Designed to meet the most rigorous production demands, the OneWrap+ combines cutting-edge technology with sturdy construction to deliver unmatched performance.

With its best-in-class load capacity of 5300 pounds, the OneWrap+ is engineered to support your heaviest loads with ease, making it the go-to solution for businesses looking to enhance their load containment process.

ONEWRAP+ SPECIFICATIONS

Maximum Capacity	5300 pounds (2400 kg)
Maximum Load Height	87" (2200 mm)
Turntable Diameter	65" (1650 mm)
Max Rotational Speed	12 RPM
Powered Pre-Stretch	250%
Operating Temperature	40 - 105 F (5-40 C)
Film Roll Specs (max)	20" W x 12" Dia x 150 GA, 45 Lbs, 3" core (fixed)
	500mm W x 300mm Dia x 35 micron, 20 kg, 76mm core

FEATURES

- SAFETY FIRST**
Safety is at the forefront of the OneWrap+ design. Fully CE compliant, it incorporates various safety measures to protect operators and maintenance personnel, making it a safe choice for your workplace. Additionally, utilizing the OneWrap+ eliminates manual wrapping and the associated potential for workplace injury.
- ROBUST DESIGN AND RELIABILITY**
Built to last, the OneWrap+ features a heavy-duty octagonal tube structure that delivers long-term reliability even under the toughest conditions. Its superior load capacity maximizes flexibility, providing you with a dependable solution that keeps your operation running smoothly.
- INTUITIVE OPERATION**
Simplify your stretch wrapping process with the OneWrap+'s intuitive icon-based control panel. Designed for ease of use, it allows operators of all skill levels to master the machine quickly, reducing training time and enhancing productivity.
- ENHANCED PRODUCTIVITY AND PROTECTION**
Transition from slow and inconsistent manual wrapping to the speed and repeatability of the OneWrap+. This machine increases throughput and minimizes labor while ensuring each load is securely wrapped for transit.
- CUSTOMIZABLE SETTINGS**
The OneWrap+ has 5 operational modes with parameters that can easily be adjusted to optimize performance based on your particular load requirements. These settings can be saved to create up to 10 unique recipes for easy recall.
- COST EFFICIENCY MEETS SUSTAINABILITY**
Equipped with a 250% powered pre-stretch carriage, the OneWrap+ not only reduces film cost, but it also supports your sustainability goals by minimizing the amount of plastic film used in your wrapping process.

CONTROL PANEL



MOVEABLE FROM FRONT OR REAR



POWERED PRE-STRETCH CARRIAGE



ROBUST STRUCTURE



