

21ST CENTURY STRETCH WRAPPING

TECHNOLOGY AND PERFORMANCE





OVERVIEW

Welcome to the next generation of stretch wrapping with the ProWrap.

This system combines cutting edge innovation with robust mechanical design to create a truly unique wrapping solution.

Offering best-in-class load capacity, unmatched customization capability, and remote connectivity features, customers that invest in the ProWrap are future-proofing their wrapping process with a system that delivers maximum reliability, safety, and cost efficiency.

EXPLORE THE ADVANCED CAPABILITIES OF PROWRAP

Experience the difference of the ProWrap’s advanced design by contacting us for more details or to schedule a demonstration

Discover how integrating this smart, powerful solution into your process can transform your packaging operations.

PROWRAP SPECIFICATIONS

Maximum Capacity	5300 pounds (2400 kg)
Maximum Load Height	118" (3000 mm)
Turntable Diameter	65" (1650 mm)
Max Rotational Speed	12 RPM
Powered Pre-Stretch	Up to 400% adjustable through HMI
Operating Temperature	40 - 105 F (5-40 C)
Film Roll Specs (max)	20" W x 12" Dia x 150 GA, 45 Lbs, 3" core (fixed)
	500mm W x 300mm Dia x 35 micron, 20 kg, 76mm core

FEATURES

- SAFETY FIRST**
Safety is paramount in the design of the ProWrap. Fully CE compliant, it incorporates various safety measures to protect operators and maintenance personnel, making it a safe choice for your workplace. Additionally, utilizing the ProWrap eliminates manual wrapping and the associated potential for workplace injury.
 - ROBUST DESIGN AND RELIABILITY**
Constructed with a heavy-duty octagonal tube structure and over-sized motors, the ProWrap is built to last and perform under the toughest conditions. In addition to capability, its exceptional load capacity of 5300 pounds also speaks to the overall build quality compared to other options on the market.
 - VERSATILITY AND CUSTOMIZATION**
Tailor your wrapping process like never before. The ProWrap offers sophisticated control over wrapping parameters across different areas of the load, enabling precise film application and optimal performance while minimizing cost. The system is capable of 5 operational modes and storing up to 12 job recipes for easy recall. If your load profile can vary from pallet to pallet, the ProWrap provides all the tools necessary for optimal containment.
 - INTUITIVE TOUCHSCREEN CONTROL**
The ProWrap comes equipped with a 7” touchscreen HMI, a significant upgrade from traditional interfaces. This user-friendly design minimizes training and simplifies operations, allowing for quick adjustments and easy access to a wide range of programmable options.
 - INTELLIGENT DUAL-MOTOR FILM DELIVERY SYSTEM**
The ProWrap uses an exclusive dual-motor carriage capable of providing up to 400% film pre-stretch which is adjustable directly through the touchscreen eliminating the need for mechanical gearing changes to adjust pre-stretch levels. The system delivers precise film pay out minimizing cost while providing consistency from load to load to ensure your products arrive safely. No matter which stretch film you use, the ProWrap can deliver the best performance now and in the future should you decide to make a change.
 - OPTIRUN REMOTE CONNECTIVITY**
Elevate your operational awareness with OptiRun technology. This system enables real-time monitoring of machine productivity statistics and film usage. Additionally, this connected service facilitates remote setup, diagnostics, and troubleshooting to ensure optimal efficiency and reduced downtime.
- Currently available in Europe, the OptiRun service will be expanded to North America, but all ProWrap units ship standard with the hardware necessary to make the connection, so you’ll be ready when we are.

7” TOUCHSCREEN



MOVEABLE FROM FRONT OR REAR



DUAL MOTOR CARRIAGE



ROBUST STRUCTURE



