

HORIZONTAL LOADERS

SIDE LOAD CASE PACKING



HLI
*Inline Horizontal Loader with
 Integrated Case Erector and Sealer*



HL
Integrated Case Erector

HORIZONTAL LOADER MODELS				
SPECIFICATIONS	HL	HL XL	HLI	HL SA
Integrated Case Erector	Y	Y	N	N
Max. Speed	6 CPM	6 CPM	6 CPM	8 CPM
Max. Case Range	20" x 13.5" x 19.5"	30" x 20" x 32"	24" x 16" x 24"	20" x 20" x 20"
Min. Case Range	8.5" x 4.75" x 4"	13" x 7.75" x 6"	13" x 7.75" x 12"	12" x 12" x 4.5"
Magazine Capacity	50" ~150 Cases	50" ~150 Cases	N/A	N/A
Case Modification Available	Y	Y	N/A	N/A
Glue Option	N	N	N/A	N/A
Washdown Option	IP54	IP54	IP54	IP54
Std. Voltage	240V/3PH	240V/3PH	240V/3PH	240V/3PH
SCFM - 80 PSI - 3/4 Supply Line	27.10 SCFM	27.10 SCFM	12.89 SCFM	12.89 SCFM
Footprint	18' x 16'2" x 7'1"	20'8" x 16'4" x 7'1"	12'5" x 3'1" x 6'10"	11'8" x 7'7" x 4'9"
Approx. Shipping Weight	~4000 lbs.	~5000 lbs.	~2500 lbs.	~2500 lbs.
Std. Finish	Steel Plus 316 is a two component, water base epoxy filled with 316 stainless steel flake. Finish Color is a Steel-It Grey and is USDA and FDA accepted.			
Controls	AB COMPACT - RS LOGIX 5000 - PV+7 HMI			
Available Options	Low Case, Low Tape, Extended Magazine, Stack Lights, Spare Parts			